

H910 Plus Flat-folded Disposable Mask

Product Description



H910 Plus Industrial Edition Flat Folding Mask is a particulate protective mask. It has a high degree of protection, larger chamber space, better air permeability, comfort and applicability, to provide users with a safe and comfortable particle protection solutions.

- Filter efficiency exceed 98%, over the National Standard
- Hidden nose clip is provided with no metal exposure, higher bending resistance than metallic material.
- Nose pad is made with sealing material of high fitness and softness, which can reduce the nasal oppressive feeling, and brings your better and more comfortable experience while using
- Large internal space enhances more air circulation, provides user comfortable
- Exhalation valve on H910V Plus can effectively discharge the heat and moisture when breathing, which reduces heat building up in the mask, thus greatly improving the comfort of wearing
- Individual pack contains 2 masks per bag, provides user more convenient and safe from contaminants

Recommended Industries/Use

Construction, mining, textile, manufacturing, wood processing, pharmaceutical, electronic, automobile manufacturing and other industries that require particles protective situations, PM2.5 protection for haze days.

Technical Specification

Shelf Life: 3 years from date of manufacture

Storage Condition: temperature range is -20 °C to 38°C, maximum relative humidity < 80%

Material Composition:

Part	Material	Advantage
Outer Layer	Polypropylene	Primary Filter, intercept the large size particles
Filter Layer 1	Polypropylene	Absorb large particles and providing heat preservation
Filter Layer 2	Polypropylene	Absorb medium-size particles and suspending small particles
Inner Layer	Polyester	Fit to skin, enhance comfort
Nose Pad	Polyester	High adhesion, reduce the leakage risk, reduce the constriction to nose, more comfortable
Ear / Head Strap	Polyester with no Latex	Hardly cause skin irritation, safer than rubber
Nose Clip	Hidden-type high strength plastic composite material	No metal exposure, bending times is 1.5 times of metallic one

Ordering Information

SKU	Description	Packaging
H1009101	H910Plus KN95 Disposable Mask, White, Ear loop, Independent Package	50 EA / box 12 Boxes/Carton
H1009102	H910Plus KN95 Disposable Mask, White, Head strap, Independent Package	50 EA / box 12 Boxes/Carton
H1009101V	H910Plus KN95 Disposable Mask with Valve, White, Ear loop, Independent Package	25 EA / box 12 Boxes/Carton
H1009102V	H910Plus KN95 Disposable Mask with Valve, White, Head strap, Independent Package	25 EA / box 12 Boxes/Carton

Use Instructions



1. Failure to follow all instructions and limitations concerning the use of respirator and/or failure to wear the respirator for the whole duration of exposure to contaminants can seriously reduce the performance characteristics of the respirator and lead to illness, injury, or death.
2. Before use, the wearer must first be trained by the employer in the correct use of the respirator in accordance with applicable safety and health standards.
3. Discard the respirator and replace with a new one if:
 - Excessive clogging of the respirator causes breathing difficulty.
 - The respirator becomes damaged.
4. Leave the contaminated area if dizziness, irritation or other distress occurs.

Use Limitations

1. DO NOT use the respirator or enter or stay in a contaminated area under the following circumstances
 - Atmosphere contains less than 19.5% oxygen
 - Atmosphere contains oil aerosols
 - For protection against gases or vapors
 - Contaminants or their concentrations are unknown or immediately dangerous to life or health

- Concentrations or contaminants exceed maximum use concentrations in applicable government regulations or 10 times the PEL (Permissible Exposure Limit), whichever is lower
 - For sandblasting, paint-spray operations, asbestos
2. DO NOT modify or misuse the respirator.
 3. DO NOT use the respirator with beards or other facial hair that interferes with direct contact between the face and the edge of the respirator, or any other conditions that may prevent a good face-seal.

Wearing Instruction

<ol style="list-style-type: none"> 1. Hold the masks of nose clip side, with nose clip up and headband naturally hanging down; 2. Put on the mask and place the chin in the mask to keep close to the face. Pull the lower end of the headband till to the back of the head, under the ears; 3. Then pull the upper end of headband to the back of the head, above the ears; 4. Press the nose clip to adjust with index finger and middle finger of both hands until it snaps close to the bridge of the nose; 5. Conduct air tightness test. 	 <p>The illustration consists of five numbered panels: 1. A person holds the mask by the sides with the nose clip up. 2. The person places the mask on their face and pulls the bottom strap behind their ears. 3. The person pulls the top strap over their head. 4. The person uses their fingers to press the nose clip against the bridge of their nose. 5. The person looks forward, wearing the mask.</p>
<p>Follow the following steps when wearing an ear loop mask:</p>	
<ol style="list-style-type: none"> 6. Put nose clip outwards. Use both hands to pull each side's ear loop and make sure the nose clip faces upwards; 7. Put on the mask, place the chin in the mask and buckle the ear loop in the back of ears; 8. Adjust to the comfortable position and make the mask close to the face; 9. Press the nose clip to adjust with index finger and middle finger of both hands until it snaps close to the bridge of the nose; 10. Conduct air tightness test. 	 <p>The illustration consists of five numbered panels: 1. A person holds the mask by the ear loops. 2. The person places the mask on their face and pulls the ear loops behind their ears. 3. The person adjusts the mask on their face. 4. The person uses their fingers to press the nose clip against the bridge of their nose. 5. The person looks forward, wearing the mask.</p>
<p>Air tightness test (as shown in Figure 5, testing tightness between the mask and face):</p>	
<ol style="list-style-type: none"> 1. Close your fingers and place your hand on the mask. Do not move the mask; 2. Inhale hard and hold your breath for a few seconds. You will find obvious inward collapse of the mask; 3. Exhale hard and hold your breath for a few seconds. You will find a clear expansion of the mask; 4. If the leak is detected, recheck again following the 1-3 step until the requirements of step 2 and 3 are met at the same time; 5. Only the respirator, which completely passes test of step1-3, can meet the air tightness requirements of the protective mask. 	

For more information

www.honeywellsafety.com

www.honeywell.com

H910P_DS | 03/18/YR
© 2016 Honeywell International Inc.

Honeywell