

RUSH PLUS



1662301 • Clear Lens



1662302 • Smoke Lens



1662306 • ESP Lens



1662310 • Twilight Lens



1662318 • Contrast Lens



Alternative colour temples are available on moqs.



Accessories:
1662320 • Gasket kit with strap

 **PLATINUM**



27 g

- + UPPER PROTECTION
- +  PLATINUM COATING ()
- + CO-INJECTED, ULTRA-FLEX TEMPLES
- + NON-SLIP BRIDGE

bolle
SAFETY

RUSH PLUS

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH PLUS	 Clear	1662301	IO & b	AS/NZS 1337.1.2010	AF / AS / Platinum P
	 Smoke	1662302	I3 & b	AS/NZS 1337.1.2010	AF / AS / Platinum P
	 ESP	1662306	I1 & b	AS/NZS 1337.1.2010	Hard Coat
	 Twilight	1662310	I1 & b	AS/NZS 1337.1.2010	AF / AS / Platinum P
	 Contrast	1662318	I1 & b	AS/NZS 1337.1.2010	Hard Coat
	 Gasket kit with strap	1662320		ZIO	AS/NZS 1337.1.2010

LENS MARKING

P. This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.

I. The letter 'I' signifies 'Medium Impact' approval.

O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

b. Manufacturer name

OCULAR LENS CATEGORY:

O. Range of luminous transmittance 80-100% (clear).

1. Range of luminous transmittance 43 -88% (twilight & ESP).

3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory

MAIN MARKETS

- Manufacturing
- Medical and dental
- Petrochemical
- Food industry
- Construction
- Government
- Mining

LENSES

- 2mm polycarbonate
- 2mm polycarbonate
- 'ALS' anti-fog/anti-scratch coating on both sides of lens: Clear and Smoke
- Hard coating on Contrast and ESP lens
- 100% UV 385 – Clear
- 100% UV 400 – Smoke, Contrast, ESP and Twilight

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	Yes
FOAM	Yes
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz